



Nennquerschnitt cross-sec.	Farbe Colour	ca. Außen-Ø approx. outer Ø	Cu-Zahl Copper content	Gewicht Weight	Bestell-Nr. XBK-code
mm <sup>2</sup>		mm	kg/km	kg/km	
<b>UL-CSA-H05V2-K (1015)</b>					
0,5 (AWG22)	sw,gg,ws,bl,bn,rt	2,5	4,8	9,0	404103 . . x
0,5 (AWG22)	vio, org, dbl	2,5	4,8	9,0	404103 . .
0,75 (AWG20)	sw,gg,ws,bl,bn,rt	2,7	7,2	11,0	404104 . . x
0,75 (AWG20)	vio, org, dbl	2,7	7,2	11,0	404104 . .
1 (AWG18)	sw,gg,ws,bl,bn,rt	2,9	9,6	14,0	404105 . . x
1 (AWG18)	vio, org, dbl	2,9	9,6	14,0	404105 . .
<b>UL-CSA-H07V2-K (1015)</b>					
1,5 (AWG16)	sw,gg,ws,bl,bn,rt	3,1	14,4	19,0	404020 . . x
1,5 (AWG16)	vio, org, dbl	3,1	14,4	19,0	404020 . .
2,5 (AWG14)	sw,gg,ws,bl,bn,rt	3,6	24,0	31,0	404021 . . x
2,5 (AWG14)	vio, org, dbl	3,6	24,0	31,0	404021 . .
4 (AWG12)	sw,gg,ws,bl,bn,rt	4,2	38,4	46,0	404022 . . x
4 (AWG12)	vio, org, dbl	4,2	38,4	46,0	404022 . .
6 (AWG10)	sw, gg	4,8	58,0	66,0	404023 . . x
6 (AWG10)	ws,bl,br,rt.vio,dbl	4,8	58,0	66,0	404023 . .
10 (AWG8)	sw, gg	6,5	96,0	112,0	404108 . . x
<b>UL-CSA-X07V2-K (1015)</b>					
16 (AWG6)	sw, gg	8,6	154,0	187,0	404109 . . x
<b>UL-CSA-H07V2-K (1015)</b>					
25 (AWG4)	sw, gg	9,8	240,0	267,0	404110 . . x
35 (AWG2)	sw, gg	11,3	336,0	346,0	404111 . . x
<b>UL-CSA-X07V2-K (1015)</b>					
50 (AWG1)	sw, gg	13,5	480,0	516,0	404112 . . x
70 (AWG2/0)	sw, gg	15,6	672,0	707,0	404113 . . x
95 (AWG3/0)	sw, gg	17,8	912,0	935,0	404114 . . x

CCC max. bis 2,5 mm<sup>2</sup>. Sonderfarben auf Anfrage! CCC up to and including 2,5 mm<sup>2</sup>. Special colours on request!